RIDGED WEDGE


170 MM - DIVISIBLE







TECHNICAL DETAILS



- > Material : recycled polypropylene
- > Colour : orange
- Dimensions : 172 mm x 46 mm x 22 mm
- > Fixing tabs : 7 mm / Quantity : 2
- > Resistant to extreme temperatures from -30°C to +60°C
- > UV and frost resistant

APPLICATIONS

> The 170 mm ridged wedge is used for all kind of hardwood floor wedging action: decking, indoor and outdoor.

BENEFITS


- > Handly divisible.
- > To be used on a flat and hard (rigid) base or on a screed.
- > It can be used as single, or one on the other.
- > Can be used with JOUPLAST® flat shims due to the lugs.

Document protected by copyright. Any reproduction, copy, extraction, reuse in others publications, translation or adaptation, display, distribution or modification, in whole or in part, withou the written consent of TMP CONVERT is strictly prohibited and will be sanctioned. TMP CONVERT reserves the right to add, modify or delete information to any time without warning.



ADJUSTMENT

> From 11 to 40 mm



RESISTANCE

> Resistance to crushing test up to 2 T.

PACKING

Bucket of 50 parts [72 bucklets per pallet - Stackable]

Mixed bucket 50 x H90 - 30 x H170 [72 buckets per pallet - Stackable]

Hangable bag of 25 parts [12 bags per box - 12 boxes per pallet]

One reference of 40 parts per bag (3 bags per box - 50 boxes per pallet)

RECOMMENDATIONS

> Fixing throughout the dedicated holes.

> Fixing with adapted glue (Can be glued directly on the screed).





www.iouplast.com