

HEIGHT 40/55 MM



BENEFITS

- The diamond-shaped head enables double joisting on a single row of riser pedestals and the use of a brace before final fixing.
- 2 fixing tabs enable joists between 40 and 80 mm wide to be laid and
- Possibility to pre-set the riser pedestals using the driver bit
- Option to use a single or double screw fixing for butt joints.
- Double joisting with a 50 mm gap.
- Performed lateral solution: 2 lateral integrated riser supports.
- One-piece riser pedestal.
- Square base for easy fitting at corners.
- Self-levelling head.

APPLICATIONS

- Ideal for creating natural wooden or composite decking for pedestrian use only.
- Facilitates construction of decking on uneven or irregular ground.
- Compensates for, or can be used to create, gradients of up to 5% on all types of ground.
- Uses a specially designed system for the clean edging of timber decking.
- Enables the laying and centring of joists between 40 and 80 mm wide.
- Enables double joisting with a single row of riser pedestals.


RESISTANCE

• Resistance to crushing test exceeds 1T.

RECOMMENDATIONS

- Terraces and patios for pedestrian use only.
- Outdoor use only.
- To bring the joist into contact with the fixing tabs, rotate the riser pedestal head anticlockwise.





© TECHNICAL DETAILS

- Material : recycled polypropylene
- Colour : black, green
- Adjustable height: mini.: 40 mm / maxi.: 55 mm
- Dimensions of the base: 192 mm x 192 mm Bearing contact area> 300 cm²
- Support surface : 117 cm² • Vertical lugs height: 25 mm
- Weight: 0,343 kg
- Resistance to temperature from -30°C to +60°C
- UV and frost resistant



• Box of 20 parts (18 boxes per pallet - Stackable)















