



Jouplast®

URBANIT®

## PAVING BLOCKS TILE FOR PERMEABLE URBAN AREAS STAGGERED INSTALLATION



### BENEFITS

- A 100% recycled material for reduced environmental impact.
- Quick and easy to lay.
- Optimal, natural drainage of rainwater.
- Integral interlocking system for maximum stability.
- Creativity: the option of combining block paving of different colors.
- URBANIT® block paved surfaces facilitate access for people with reduced mobility.



### APPLICATIONS

- Perfect for creating forecourts, access roads or pedestrian and cycle paths etc... (in city centres, shopping centres and many other applications).
- Perfect for pedestrians and permeable paths for private use.
- 100% permeable to rainwater.
- Used for alignment when laying paving blocks.
- Facilitates access for bicycles and pushchairs.
- Suitable for use by vehicles with axle loadings of up to 20 tonnes.
- Suitable for creation of fire access roads.



### RESISTANCE

- Vertical resistance (filled): resistance equivalent to T5 class for paving block (standard in force in France)




### RECOMMENDATIONS

- Type of block paving recommended: 15 x 15 cm x 6 cm high. Please contact your local sales consultant for a list of compatible paving blocks brands.
- Allow 40 paving blocks per m<sup>2</sup>.
- The Urbanit® range is not designed for intensive use by heavy goods vehicles.
- Do not use with hot mixed asphalt.
- Do not drive over empty modules.
- Can be installed on slopes up to 2%.
- Aggregate graded to between 2 (min.) and 5 (max.) can be added above the joints.
- For IFU, see the website.



TECHNICAL DATA SHEET



### TECHNICAL DETAILS

- Material: recycled polyolefin
- Colour: black
- Usable dimensions: 476 mm x 319 mm x 57 mm \*
- Usable area: 0.1518 m<sup>2</sup> (6.5876 tiles per m<sup>2</sup>)
- Overall dimensions: 480 mm x 322 mm x 57 mm \*
- Width of joint between paving block: 7.5 mm
- Weight: 0.518 kg ie 3.40 kg/m<sup>2</sup>
- Resistance to temperature from -30°C to +60°C
- UV and frost resistant



### PACKING

- Pallet of 138 parts i.e 20.9484 m<sup>2</sup> (Stackable)
- Full truck = 1 089,3168 m<sup>2</sup> (52 stackable pallets ie 26 palettes on the floor)



### USE

- Urbanit® is fully compliant with the required puncture resistance of 80 N/cm<sup>2</sup> for fire access applications.

Document protected by copyright. Any reproduction, copy, extraction, reuse in others publications, translation or adaptation, display, distribution or modification, in whole or in part, without the written consent of TMP CONVERT is strictly prohibited and will be sanctioned. TMP CONVERT reserves the right to add, modify or delete information to any time without warning.



www.jouplast.com



\* Manufacturing tolerance: +/- 1%

FT\_URBANIT\_02407\_EN