Jouplast®

PAVING RISER PEDESTAL

TECHNICAL DATA SHEET



ADJUSTMENT IN HEIGHT FROM 40 TO 60 MM «ESSENTIAL» RANGE

100% recycled



BENEFITS

- Quick and easy installation.
- Precise height adjustment using the rotating nut: no additional tools required.
- Divisible spacers for staggered laying.
- Base shape optimised: makes it easy to lay paving against a wall or in a corner.

APPLICATIONS

- Ideal for creating paved or ceramic tiled outdoor terraces for pedestrian use only.

RESISTANCE

- Resistance to crushing test exceeds 1T.

RECOMMENDATIONS

- Terraces and patios for pedestrian use only.
- Outdoor use only.
- Always follow paving manufacturer recommendations to ensure the suitability of paving products for use with riser pedestals and the number of risers per m² to use. Qualification of compulsory "SELF-SUPPORTING" slabs, of class T7, T11 according to standard EN 1339:2004-02.
- Paving riser pedestals should be used only on stabilised level ground or on existing concrete support.
- Not compatible with 60 mm extension.
- When the riser pedestal is used at its highest position, we recommend adding a 10 mm extension to provide greater flexibility during adjustment.
- When the riser pedestal is used at its lowest position, we recommend using the rised pedestal of the next size dowm, adding a 10 mm extension for greater flexibility when adjusting.
- Acoustic rubber cushion not included.
- For IFU, see the website.

TECHNICAL DETAILS

- Material: recycled polypropylene
- Colour: black, blue nut
- Adjustable height: mini.: 40 mm / maxi.: 60 mm
- Spacer: height: 12 mm / thickness: 3 mm / qty: 4
- Basis diameter: 198 mm / Bearing contact area: 300 cm²
- Support surface diameter: 120 mm / Bearing contact area: 100 cm²
- Weight: 231 g
- Resistance to temperature from -30°C to +60°C
- UV and frost resistant

PACKING

- Filmed in packs of 11 (Pallet of 60 packs - Stackable pallet)

Document protected by copyright. Any reproduction, copy, extraction, reuse in others publications, translation or adaptation, display, distribution or modification, in whole or in part, without the written consent of TMP CONVERT is strictly prohibited and will be sanctioned. TMP CONVERT reserves the right to add, modify or delete information to any time without warning.